


# COLOR DOME CAMERA

**PROVIDEO**

speco technologies

**MODEL:CVC-6405DC**

## VARIFOCAL LENS 4mm -- 9mm



### GENERAL FEATURES

- COLOR CCD 1/4" FORMAT
- LOW POWER CONSUMPTION
- REQUIRES 0.92 LUX FOR LOW LIGHT APPLICATIONS
- BUILT IN ELECTRONIC AUTO IRIS
- HIGH RESOLUTION
- INTERNAL SYNCHRONIZATION
- VARIFOCAL LENS 4mm- 9mm

### SPECIFICATIONS

MODEL NO	CVC-6405DC
IMAGE SENSOR	INTERLINE TRANSFER CCD 1/4" FORMAT
EFFECTIVE PIXEL	512(H) x 492(V) PIXELS/NTSC 512(H) x 582(V) PIXELS/PAL
SCANNING SYSTEM	2:1 INTERLACED
SYNC SYSTEM	INTERNAL SYNC
SYNC PULSE	15.734KHz $\pm$ 1% (H) / 15.625KHz $\pm$ 1% (H) 59.94KHz $\pm$ 1% (V) / 50KHz $\pm$ 1% (V)
RESOLUTION	SUB-CARRIER 3.57 MHz $\pm$ 30ppm
MINI ILLUMINATION	420 TV LINE(H)
S/N RATIO	0.92 Lux F1.2
WHITE BALANCE	MORE THAN 48dB
VIDEO OUTPUT	AUTO WHITE BALANCE
ELECTRONIC SHUTTER TIME	COMPOSITE VIDEO SIGNAL: 1.0Vp-p 75 ohm
POWER SUPPLY	NTSC=1/60- 1/100,000 Sec PAL=1/50-1/100,000 Sec
POWER CONSUMPTION	12 VOLTS DC-CENTER PIN POSITIVE
LENS	160mA(TYP)
OPERATIONAL TEMP.	VARIFOCAL LENS 4mm- 9mm
STORAGE TEMP.	-50 — 122° F
DIMENSION	-68 — 144° F
WEIGHT	2.7" (H) x 4 5/8" (W) x 4 5/8" (D)
	7.4 oz (210grams)

Specifications subject to change

Speco Technologies-ProVideo

200 NEW HIGHWAY

AMITYVILLE, N Y 11701

1-800-645-5516 1-631-957-8700

Always use discretion when installing video and/or audio surveillance equipment especially when there is perceived privacy. Inquire regarding federal, state and/or local regulations applicable to the lawful installation of video and/or audio recording or surveillance. Party consent may be required.